PMXTREME®

Optimal Style In Safety Eyewear





Part

Part

SCM6310STP•

SCM6318STP•

SCM6320STP•

SR6320SP•

Red Frame with Black Cord

Lens

Lens

Gray

Clear Anti-Fog

Gray Anti-Fog

Sandstone Bronze Anti-Fog

Part Lens

SB6310SP• Clear

SB6310STP • Clear Anti-Fog

SB6320SP • Gray

SB6320STP • Gray Anti-Fog

SB6330SP• Amber

SB6345SP• Ice Orange Mirror

SB6360SP• Infinity Blue

SB6370SP Silver Mirror

SB6375SP• Blue Mirror

SB6376SP• Smoke Green Mirror
SB6380SP• Indoor/Outdoor Mirror

• Built-in rubber nose piece provides all day comfort.

· Includes black lanyard cord for extra security while wearing.

- Rubber temple tips keep eyewear secure for the active worker.
- Extreme style in safety eyewear, with clean lines and sports appeal.
- · Ventilated, straight-back flexible temples provide cool, pressure-free fit.
- Scratch resistant polycarbonate lenses provide maximum vision protection, filter out 99% of harmful UV rays.

GENERAL SPECIFICATION	
Bridge: 14mm	
Lens Base: 9 Curve	
Lens Size Diagonal: 78mm	
Lens Size Vertical: 46mm	
Lens Thickness: 2.2mm	
Overall Length (Lens-Tip): 103mm	
Overall Width (Hinge-Hinge): 140mm	
PD: 72mm	
Weight: 27gm	



PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES	
Lens	Polycarbonate	9 base curve, molded lens attached to the frame	
Frame	Nylon	Half Frame	
Nose Piece	Rubber	N/A	
Sleeve (on temples)	Hard Rubber	N/A	
Temple	Nylon	N/A	
Hinge Screw	Nickel Silver	Standard hinge screw	

PART	LENS	LENS MARKING	FRAME MARKING
SB6310SP	Clear	P + U6	P Z 8 7 +
SB6310STP	Clear (Anti-Fog)	P + U6	P Z 8 7 +
SB6320SP	Gray	P + U6 L3	P Z 8 7 +
SB6320STP	Gray (Anti-Fog)	P + U6 L3	P Z 8 7 +
SB6330SP	Amber	P + U6	P Z 8 7 +
SB6345SP	Ice Orange Mirror	P + L3	P Z 8 7 +
SB6360SP	Infinity Blue	P + U6 L1.3	P Z 8 7 +
SB6370SP	Silver Mirror	P + U6 L1.3	P Z 8 7 +
SB6375SP	Blue Mirror	P + U6 L1.3	P Z 8 7 +
SB6376SP	Smoke Green Mirror	P + U6 L1.3	P Z 8 7 +
SB6380SP	Indoor/Outdoor Mirror	P + U6 L1.7	P Z 8 7 +
SCM6310STP	Clear	P + U6	P Z 8 7 +
SCM6318STP	Sandstone Bronze	P + U6 L2.5	P Z87 +
SCM6320STP	Gray	P + U6 L3	P Z87 +
SR6320SP	Gray	P + U6 L3	P Z87 +

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

- +: High Impact
- H: Small Head Size
- S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7% U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3% U3: Max Effective Far UV= .07% / Max Near UV= 1.4% U4: Max Effective Far UV= .04% / Max Near UV= .5% U5: Max Effective Far UV= .02% / Max Near UV= .2% U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light L1.7: 55% Max. Visible Light L2.5: 29% Max. Visible Light L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact